


MT15 Series



Model		MT15-xxx
LCD Display		15" TFT
Display Size (HxV mm)		304.1 x 228.1
Pixel Pitch (HxV mm)		0.297 x 0.297
Max. Resolution (acceptable)		XGA 1024x768
Contrast Ratio		400:1
Brightness		250 cd/m ²
Response Time		16 ms (Typical)
Display Color		162K
Viewing Angle	H/V	+130°~-120°
PC Interface	Video	RGB analog (75Ohms, 0.7Vp-p)
	Sync.	H/V separated (TTL) positive/negative
Audio (Option)		Stereo Mini-Audio Line-In
		2 x 2.5W speakers
Touch Screen		Capacitive Type / Resistive Type (4Wire, 5Wire, 8Wire)
Touch Screen Interface		Serial(RS232)/USB
Digital Interface	Analogue	D-sub 15 Pin (VGA)
Power	Form	Imbedded universal power/ AC/DC Adapter Input AC 100~240V, 50~60Hz, Output DC 12V/3A
	Consumption	40W (MAX.)
Key Controls		Power on/off with LED, Menu, Select, Sdjustment (+,-)
Operating Condition	Temperature	0°C-40°C (32°F-104°F)
	Humidity	10%-90% (no condensing)
Safety & EMI		UL/CE/FCC/TUV/GS
Dimensions (HxWxD mm)		347 x 343 x 180

*Specifications are subject to change in different panel used.



燦微科技股份有限公司
Transpoint Technology Incorporated.

台北縣汐止世新台五路一段77號18樓之五
TEL : (02) 2698-8072 FAX : (02) 2698-8092

www.transpoint.com.tw